

SY35U

Flexible and Energy-saving
High Quality

CHANGES THE WORLD

Quality changes the world



Selling Points

Good Controllability

With matured load sensing system, and debugging technology, the machine possesses excellent controllability.

Stable & Reliable

With reinforced working device and high-strength slewing platform, the overall performance is more stable and reliable.


High Efficient & Energy Saving

With independently developed intelligent control system, the engine matches with the maim pump perfectly, the working efficiency is higher and the fuel consumption is lower.

Safe & Comfortable

With standard operator cabin, and dual-purpose air conditioner, the operations become safer and more comfortable.





A Overall length (in transportation state)	SY35U)4915
B Overall width (in transportation state /in operation state)	1720
C Overall height (in transportation state)	2515
D Height of bulldozing plate	350
E Width of standard track shoe	300
F Track gauge (in transportation state / in operation state)	1420
G Minimum ground clearance	295
H Slewing radius of tail	860
I Ground contact length of track	1670
J Track shoe length	2155

Performance parameters	Standard
	SY35U
Total weight, kg	3780
Bucket capacity m³	0.06-0.15(0.12)
Rated power, kW/rpm	20.2/2200
Traveling speed (high/low), km/h	4.4/2.4
Slewing speed, rpm	9
Gradeability	58%
Ground pressure, kPa	32
Digging force of bucket, kN	30.4
Digging force of bucket rod, kN	18.2

Operating range (mm)

ft	m											
20 -	6											
15 -	5				- f					+		
	4						5					
10 -	3								H			
	2						9		\ b	a		
5 -	1						1					
0 -	0	hj				la la		M				
	-1	1,1		1	7				\mathbb{Z}			
-5 -	-2								d	c		
					е	1						
-10 -										+		
_15 _	-4											
	25 25	-2 -1	() 1		2	3	4	5	6	7	m
	25	- <u>2 -1</u> 20)	15		10	5		0		-5	ft

Standard

	SY35U
a Maximum digging height	4855
b Maximum unloading height	3460
c Maximum digging depth	3105
d Maximum digging depth with vertical boon	n 2700
e Maximum digging distance	5465
f Minimum slewing radius	2475
g Maximum height at maximum slewing radius	3685
h Maximum ground clearance with bulldozing plate lifted u	лр 375
i Maximum cutting depth of bulldozing plate	370

A SANY Heavy Machinery Co., Ltd.

SANY Industrial Park, Dongcheng Avenue, Kunshan Economic & Technological Development Zone, Jiangsu Province Post code: 215300

After-sales service hotline: 4008-28-2318 Consulting & complaint hotline: 4008-87-9318 Website: http://www.sanygroup.com

